


MICRO CO2 KIT

PLANTED AQUARIUM ACCESSORY

ULTIM NATURE SYSTEMS



SETUP GUIDE

Please follow the instructions below for safe CO2 regulator setup:

1. Turn pressure adjustment knob clockwise all the way down. This is indicated by the "OFF" sign respectively.
2. Attach the regulator directly to the desired CO2 cartridge. Hand-tighten the connection and ensure it is fully secure.

IMPORTANT! DO NOT STOP TIGHTENING WHEN GAS IS LEAKING ONCE PINHOLE IS PUNCTURED IN CARTRIDGE. CONTINUE TIGHTENING ALL THE WAY UNTIL GAS STOPS LEAKING.

- 3 - 5. Attach the solenoid and bubble counter. Ensure all connections are secure and tightened. Then, fill bubble counter with water from the integrated opening.








Note: Pressure-Proof CO2 Tubing should also be attached during this time.

6. Connect the Power Plug to the regulator solenoid cable FIRST. Secure the connection, then plug into a power outlet.

7. Open the flow of gas from CO2 cartridge by adjusting the pressure adjustment knob counter-clockwise.

8. CO2 bubbles should now be visible in the Bubble Counter chamber.

IMPORTANT! Double check that any and all additional CO2 accessories are attached securely before operation. If unsure, check and repeat instructions.

<p>STEP 1</p> 	<p>STEP 2</p> 
<p>STEP 3</p> 	<p>STEP 4</p> 
<p>STEP 5</p> 	<p>STEP 6</p> 
<p>STEP 7</p> 	<p>STEP 8</p> 